Restaurant Details

Food Service Establishment Permit(FSEP)

FSEP#: **41599272** Expiration Date: **06/30/2024** DOHMH Status: **CURRENT** Business Legal Name: **SEQUOIA TREE LLC** Assumed Name: **LE MOULIN A CAFE** Business Address: **1439 YORK AVENUE, NEW YORK, NY 10075**

Restaurant Information

Entity Type: **Partnership** Employer Identification Number: **26-4791904** Phone: **(212) 288-5088** Email Address: **lemoulinny@gmail.com**

Emergency Contact Information

First Name: **Yann** Last Name: **N'Diaye** Phone: **(917) 459-9550** Email Address: **yann17@cs.com**

NYS Liquor Authority Information

NYSLA Serial No: **890973** License Type: **On-Premises** Name of License: **Yann NDiaye** Title of Representative: **Owner** Name of Certificate Holder: **Yann NDiaye**

User Information

Created By: Yann Ndiaye Created On: 3/12/2024 2:12:28 PM Modified By: Yann Ndiaye Modified On: 4/24/2024 5:23:27 PM

Business hours

Sun: 8:00 AM- 5:00 PM Mon: 7:30 AM- 6:00 PM Tues: 7:30 AM- 9:00 PM Wed: 7:30 AM- 9:00 PM Thurs: 7:30 AM- 9:00 PM Fri: 7:30 AM- 10:00 PM Sat: 8:00 AM- 10:00 PM

DINING OUT NYC

COMMUNITY BOARD RECOMMENDATION FORM

This form is to be used by community boards during the cafe review process. Any comments from the community board should be recorded on this form and submitted to NYC DOT. For information pertaining to specific cafe design requirements, visit the Dining Out NYC website for program legislation, rules, and Setup Guides.

Business Name: Le Moulin a Cafe

Cafe Location: 1439 YORK AVENUE, NEW YORK, NY, 10075

Application Number: 20240319010002

Recommendation Response Deadline: 8/21/2024

NYCDOT Internal Use Only

Roadway Cafe Setup Comments:

Comments related to the cafe's physical footprint and dimensions:

Comments related to **pedestrian flow** (i.e., visbility, safety , potential crowding):

Comments related to potential conflicts with existing curb use (i.e., planters, bike racks, bus stops):

Overall recommendation for the cafe setup:

Suggested modifications related to the above referenced application:

NEW YORK CITY Eric Adams SECTION 1: Site Plan Ydanis Rodriguez This Site Plan form is required to be uploaded in the "Roadway Site Plan" field of your online application. Refer to the How to Apply page in the Dining Out NYC website for more information about the application process. . **Roadway Cafe** Identify Permitted Parking Location: Site Plan Form Identify the Parking Sign in front of or around the area where your roadway setup would be located. VANN Roadway cafes can only be placed in: Applicant Name: Parking spaces, which include: metered and non-metered spaces, commercial parking, alternate side parking, angled parking. P1- Parking Space Restaurant Name: LE MOULIN A CAFE and seasonally restricted parking. 2. Loading areas, including loading only, truck loading, hotel loading, and no parking zones. P2- Loading Area 41599272 3. Floating Parking Lane- a parking lane that is separated from the curb by a protected bicycle lane that is adjacent to the curb. FSEP Number: P3- Floating Parking Lane Use the space below to draw or upload your Site Plan representing your cafe perimeters, furniture, and clearances, **Drawing Requirements** Food service establishment frontage Building reighboring Restaurant neighboring shown as: Line representing the establishment's entrance entrance. space facing the sidewalk establishment Establishment Length Label Street names: RESTAURANT FRONTAGE -20 FEET Labels on each street Sidewalk shown as: Line representing street curb SIDEWAIK SIDEWALK SIDEWALK Roadway shown as: Width of curbside lane Cafe perimeter shown as: 3FEGT Lines indicating perimeter CURB CURB CURB Length and width 0 Set-up furniture (tables, chairs, etc.) 15 FEET ALE WIDTH PARKING shown as: Lines or symbols at approximate FIRE location within setup HYDRAN Elements (in Section 2 of this form) OFIC within 15 feet of cafe perimeter, shown as: 135 17 FEET Lines or symbols K->1 FOOT 6 INCHES Distance from cafe perimeter Labels Utility coverings (water/gas valves, and NEW YORK STREET pull boxes) shown as: Symbols representing the location within the setup North arrow 17 FEET FEFT Length of roadway cafe: Width of roadway cafe:

SECTION 3: Material Requirements SECTION 2: Required Clearances Please indicate which of the following materials will be part of your roadway cafe by checking the box next Please provide distances from the following objects. to the category. If applicable, please confirm the materials comply with the Dining Out NYC requirements. Only provide a distance if the listed object is within 15 feet of your proposed setup. Refer to the Setup Guides in the Dining Out NYC website for more information regarding clearances. Refer to the Setup Guides in the Dining Out NYC website for more information regarding materials. Elements with minimum 15 feet clearance from roadway cafe: Materials Checklist: 15 feet R01- Subway Stair: Open End R02- Fire Hydrant *Required* Barriers (All of the following must be met) Elements with minimum 10 feet clearance from roadway cafe: Maintained on all sides of the cafe except the side fronting the ground floor restaurant. R03- Subway Elevator Entrance feet R05-MTA Curb Cut feet Not permanently affixed to the roadway. 30-42 inches tall (excluding planting), and at least 4 inches in width. R04- FDNY Curb Cut feet Barriers are interconnected with each other. Elements with minimum 5 feet clearance from roadway cafe: Any cladding over the barriers is securely fastened or affixed. Minimum 4 inches wide reflective strip on each barrier on the outward facing side. R11- CitiBike/Bike Share Station feet R06- Curb Cut feet Water-filled with a minimum of 150 pounds per linear foot of barrier length. R12- Bike Corral feet R07- Emergency Exit Hatch feet R13- Micromobility Station feet R08- Subway Stair: Closed End feet *Optional - Only check the material categories you intend to use in your roadway cafe* R09- Subway Elevator: Non-Entry feet R14- Drainage Infrastructure feet Flooring (if using, all of the following must be met) R10- Bus Stop Pole: 59 Durable, lightweight, easily removable, mold-resistant, elevated from the ground level to allow for Non-Approaching Side feet drainage, and removable to allow for cleaning. Elements with minimum 3 feet clearance from roadway cafe: Flush with the curb line (except if located on a slope, be flush to the greatest extent feasible), and compliant with applicable accessibility requirements. R16- Transformer Vault feet R15- Elevated Train Infrastructure feet Maintains a 6 inch covered channel between curb and base of flooring to allow for drainage. Elements with minimum 1 foor and 6 inches clearance from roadway cafe: Furnishings (if using, all of the following must be met) inches Lightweight and easily movable. R17-Vent Infrastructure: feet R18-Manholes utility vent poles, vent Vertical Screenings (if using, all of the following must be met) grates, subway grates Located between the barrier and 6 feet above the cafe base or floor. Elements with minimum 6 inches clearance from roadway cafe: Located on the roadway facing side, does not extend the beyond the perimeter of the roadway cafe, and is not affixed to the outward facing side of barriers. R19- Thermoplastic Marking Easily removable, comprised of non-opaque, fire-grade, and wind resistant materials. If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height. Roadway cafe distance from crosswalks: Overhead Coverings/ Umbrellas (if using, all of the following must be met) R20- Adjacent to Minimum of 7 feet and maximum of 10 feet from the base or floor of the roadway cafe. non-approaching side of Whas a weighted base and any support structures are not affixed to the outward facing side of barriers, are crosswalk **Distance** required Distance required from of sufficient size and strength, made of durable materials, and free of defects. (min. 8 foot distance) crosswalk on from crosswalk on feet Easily removable, comprised of fire-grade and wind resistant materials. non-approaching side approaching side If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height. R21-Adjacent to approaching (stopping) Lighting and Electrical Connections (if using, all of the following must be met) side of crosswalk Any lighting is outdoor rated, properly secured, and lightweight. (min. 20 foot distance) feet At least 14 feet above sidewalk, and 18 feet above roadway. R22- No crosswalk present 8.0-Not attached to any City property, including street trees. (maintain 20 feet from Electrical work complies with the applicable requirements set forth in DOT's rules and the New York City curb line of intersecting Electrical Code. Please note that this may require additional permits from DOB or FDNY, and/or approval from the feet street) Landmarks Preservation Commission (LPC) as applicable.

Check this box if none of the objects listed above are within 15 feet of the proposed setup.









