



20240517010001 The Mansion

Please review this application.

DINING OUT NYC

Business Name:

The Mansion

Cafe Setup Address: 1634 YORK AVENUE, NEW YORK, NY 10028

COMMUNITY BOARD RECOMMENDATION FORM

This form is to be used by community boards during the cafe setup review process. Any comments from the community board should be recorded on this form and submitted to NYC DOT. For information pertaining to specific cafe setup design requirements, visit the Dining Out NYC website for program legislation, rules, and Setup Guides.

Application Number: 20240517010001
Recommendation Response Deadline: 8/28/2024
NYCDOT Internal Use Only
Roadway Cafe Setup Comments:
Comments related to the cafe setup's physical footprint and dimensions :
Comments related to pedestrian flow (i.e., visbility, safety , potential crowding):
Comments related to potential conflicts with existing curb use (i.e., planters, bike racks, bus stops):
Overall recommendation for the cafe setup:
Suggested modifications:



Outdoor Dining Application

Restaurant Details







I

Food Service Establishment Permit(FSEP)

FSEP#: 41153872 Expiration Date: 11/30/2024

DOHMH Status: **CURRENT**

Business Legal Name: YORKVILLE MANSION INC

Assumed Name: THE MANSION

Business Address: 1634 YORK AVENUE, NEW YORK, NY 10028

Restaurant Information

Entity Type: Corporation

Employer Identification Number: 20-3222522

Phone: (212) 535-8888

Email Address: mansion1634@gmail.com

Emergency Contact Information

First Name: John

Last Name: Philips

Phone: (646) 319-1382

Email Address: jgp1300@gmail.com

DOS Information

DOS ID#: 20322225

Process Name: ein

DOS Address: 1634 York Avenue, New York, New York 10028

NYS Liquor Authority Information

NYSLA Serial No: 1172212

License Type: On-Premises

Name of License: York ville Mansion Inc

Title of Representative: **Principal**

Name of Certificate Holder: John Philips

User Information

#

Αį

FSEP#

4115387

→ <u>20</u>

Restaurant Details

Food Service Establishment Permit(FSEP)

FSEP#: **41153872** Expiration Date: **11/30/2024**

DOHMH Status: CURRENT

Business Legal Name: YORKVILLE MANSION INC

Assumed Name: THE MANSION

Business Address: 1634 YORK AVENUE, NEW YORK, NY 10028

Restaurant Information

Entity Type: Corporation

Employer Identification Number: 20-3222522

Phone: (212) 535-8888

Email Address: mansion1634@gmail.com

Emergency Contact Information

First Name: John

Last Name: Philips

Phone: (646) 319-1382

Email Address: jgp1300@gmail.com

DOS Information

DOS ID#: 20322225

Process Name: ein

DOS Address: 1634 York Avenue, New York, New York 10028

NYS Liquor Authority Information

NYSLA Serial No: 1172212

License Type: On-Premises

Name of License: York ville Mansion Inc.

Title of Representative: **Principal**

Name of Certificate Holder: John Philips

User Information

FSEP#

4115387

Αį #

20









SECTION 1: Site Plan

- This Site Plan form is required to be uploaded in the "Roadway Site Plan" field of your online application.
- Refer to the How to Apply page in the Dining Out NYC website for more information about the application process.

Identify Permitted Parking Location:

- Identify the Parking Sign in front of or around the area where your roadway setup would be located.
- Roadway cafes can only be placed in:
 - Parking spaces, which include: metered and non-metered spaces, commercial parking, alternate side parking, angled parking and seasonally restricted parking.
 - 2. Loading areas, including loading only, truck loading, hotel loading, and no parking zones.
 - 3. Floating Parking Lane- a parking lane that is separated from the curb by a protected bicycle lane that is adjacent to the curl

rking,	P1- Parking Space
	P2- Loading Area
urb.	P3- Floating Parking Lane

Commissioner		Mayor Ydanis Rodrigue
--------------	--	--------------------------

Roadway Cafe Site Plan Form

Applicant Name:	
Restaurant Name:	
FSEP Number:	

Drawing Requirements

Food service establishment frontage shown by:

- Line representing space occupied in building
- Labels
- Length

Street names:

Labels on each street

Sidewalk shown as:

- Line representing street curb
- Width measured from building line to curb line

Roadway shown as:

- Lines indicating parking lane
- Width of parking lane

Cafe perimeter shown as:

- Lines indicating perimeter
- Length and width of all three sides

Set-up furniture (tables, chairs, etc.) shown as:

Lines or symbols at approximate location within setup

Elements or objects shown as:

- Lines or symbols
- Labels
- Distance from cafe perimeter

Utility coverings shown as:

 Symbols representing the approximate shape of the covering within the setup

Q	MANHOLE COVER
_	LITH ITY COVEDING

□ UTILITY COVERING

Use the space below to draw or upload your Site Plan representing your cafe perimeters, furniture, and clearances.						
	Use the space	below to draw or upload your Sit	te Plan represer	nting your cafe perimeters, furi	niture, and clearances.	
	-		-			- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						- 11
						H
						H
						H
						H
						l l
Length of roadway cafe:feet Width of roadway cafe:feet		Length of roadway cafe:	feet	Width of roadway cafe:	feet	

SECTION 2: Required Clearances

- Please provide distances from the following objects.
- Only provide a distance if the listed object is within 15 feet of your proposed setup.
- Leave box blank if not applicable.

(min. 20 foot distance)

(maintain 20 feet from curb line of intersecting

R21- No crosswalk present

street)

• Refer to the <u>Setup Guides</u> in the Dining Out NYC website for more information regarding clearances.

Elements with minimum 15 feet clear	rance from ro	oadway cafe:	
R01- Subway Stair: Open End R02- Fire Hydrant	feet feet		
Elements with minimum 10 feet clea	rance from ro	oadway cafe:	
R03- Subway Elevator Entrance R04- FDNY Curb Cut R05- MTA Curb Cut	feet feet feet		
Elements with minimum 5 feet cleara	ance from roa	adway cafe:	
R06- Curb Cut R07- Emergency Exit Hatch R08- Subway Stair: Closed End R09- Subway Elevator: Non-Entry R10- Bus Stop Pole: Non- Approaching Side Elements with minimum 3 feet cleara	feet	R11- CitiBike/Bike Share S R12- Bike Corral R13- Micromobility Statio R14- Drainage Infrastruct	feetfeet
		auway care.	
R15- Elevated Train InfrastructureR16- Transformer Vault	feet feet		
Elements with minimum 1 foor and 6	inches clear	rance from roadway cafe:	
R17- Vent Infrastructure Elements with minimum 6 inches cle	feet arance from	roadway cafe:	
R18- Thermoplastic Marking	feet		
Roadway cafe distance from crosswa	alks:		
R19- Adjacent to non-approaching side of crosswalk (min. 8 foot distance) R20- Adjacent to approaching (stopping) side of crosswalk	feet	Distance required from crosswalk on non-approaching side	Distance required from crosswalk on approaching side

feet

feet

SECTION 3: Material Requirements

- Please indicate which of the following materials will be part of your roadway cafe by checking the box next to the category. If applicable, please confirm the materials comply with the Dining Out NYC requirements.
- Refer to the <u>Setup Guides</u> in the Dining Out NYC website for more information regarding materials.

laterials Checklist:
Required Maintained on all sides of the cafe except the side fronting the ground floor restaurant. Not permanently affixed to the roadway. 30-42 inches tall (excluding planting), and at least 4 inches in width. Barriers are interconnected with each other. Any cladding over the barriers is securely fastened or affixed. Minimum 4 inches wide reflective strip on each barrier on the outward facing side. Water-filled with a minimum of 150 pounds per linear foot of barrier length. If your proposed barriers will utilize fill materials other than water please check this box. This may require additional information from the applicant and further review by the Dining Out NYC team, as well as supporting DOT units and City agencies.
Optional- Only check the material categories you intend to use in your roadway cafe Flooring Durable, lightweight, easily removable, mold-resistant, elevated from the ground level to allow for drainage, and removable to allow for cleaning. Flush with the curb line (except if located on a slope, be flush to the greatest extent feasible), and compliant with applicable accessibility requirements. Maintains a 6 inch covered channel between curb and base of flooring to allow for drainage. Furnishings Lightweight and easily movable.
Vertical Screenings Located between the barrier and 6 feet above the cafe base or floor. Located on the roadway facing side, does not extend the beyond the perimeter of the roadway cafe, and is not affixed to the outward facing side of barriers. Easily removable, comprised of non-opaque, fire-grade, and wind resistant materials. If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.
Overhead Coverings/ Umbrellas Minimum of 7 feet and maximum of 10 feet from the base or floor of the roadway cafe. Has a weighted base and any support structures are not affixed to the outward facing side of barriers, are of sufficient size and strength, made of durable materials, and free of defects. Easily removable, comprised of fire-grade and wind resistant materials. If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.
Lighting and Electrical Connections Any lighting is outdoor rated, properly secured, and lightweight. At least 14 feet above sidewalk, and 18 feet above roadway. Not attached to any City property, including street trees. Electrical work complies with the applicable requirements set forth in the DOT's rules and the New York City Electrical Code.

Please check this box if you are submitting additional documents for review. Documents may include technical

drawings prepared by a licensed professional.

SECTION 1: Site Plan

- This Site Plan form is required to be uploaded in the "Roadway Site Plan" field of your online application.
- Refer to the How to Apply page in the Dining Out NYC website for more information about the application process.

Identify Permitted Parking Location:

- Identify the Parking Sign in front of or around the area where your roadway setup would be located.
- Roadway cafes can only be placed in:
 - Parking spaces, which include: metered and non-metered spaces, commercial parking, alternate side parking, angled parking and seasonally restricted parking.
 - 2. Loading areas, including loading only, truck loading, hotel loading, and no parking zones.
 - 3. Floating Parking Lane- a parking lane that is separated from the curb by a protected bicycle lane that is adjacent to the curl

rking,	P1- Parking Space
	P2- Loading Area
urb.	P3- Floating Parking Lane

Commissioner		Mayor Ydanis Rodrigue
--------------	--	--------------------------

Roadway Cafe Site Plan Form

Applicant Name:	
Restaurant Name:	
FSEP Number:	

Drawing Requirements

Food service establishment frontage shown by:

- Line representing space occupied in building
- Labels
- Length

Street names:

Labels on each street

Sidewalk shown as:

- Line representing street curb
- Width measured from building line to curb line

Roadway shown as:

- Lines indicating parking lane
- Width of parking lane

Cafe perimeter shown as:

- Lines indicating perimeter
- Length and width of all three sides

Set-up furniture (tables, chairs, etc.) shown as:

Lines or symbols at approximate location within setup

Elements or objects shown as:

- Lines or symbols
- Labels
- Distance from cafe perimeter

Utility coverings shown as:

 Symbols representing the approximate shape of the covering within the setup

Q	MANHOLE COVER
_	LITH ITY COVEDING

□ UTILITY COVERING

					9 =
Use the space	below to draw or upload your Si	ite Plan represe	nting your cafe perimeters, fu	rniture, and clearances.	
•		-			
	Length of roadway cafe:	foot	Width of roadway cafe:	f	
	Length of loadway cale.		Width of Todaway Cale.	теет	

SECTION 2: Required Clearances

- Please provide distances from the following objects.
- Only provide a distance if the listed object is within 15 feet of your proposed setup.
- Leave box blank if not applicable.

side of crosswalk (min. 20 foot distance)

(maintain 20 feet from curb line of intersecting

R21- No crosswalk present

street)

• Refer to the <u>Setup Guides</u> in the Dining Out NYC website for more information regarding clearances.

Elements with minimum 15 feet c	learance from r	oadway cafe:	
R01- Subway Stair: Open End	feet		
R02- Fire Hydrant	feet		
Elements with minimum 10 feet c	learance from r	oadway cafe:	
R03- Subway Elevator Entrance	feet		
R04- FDNY Curb Cut	feet		
R05- MTA Curb Cut	feet		
Elements with minimum 5 feet cle	earance from ro	adway cafe:	
R06- Curb Cut	feet	R11- CitiBike/Bike Share Station	feet
R07- Emergency Exit Hatch	feet	R12- Bike Corral	feet
R08- Subway Stair: Closed End	feet	R13- Micromobility Station	feet
R09- Subway Elevator: Non-Entry	feet	R14- Drainage Infrastructure	feet
R10- Bus Stop Pole:			
Non- Approaching Side	feet		
Elements with minimum 3 feet cle	earance from ro	adway cafe:	
R15- Elevated Train Infrastructure	feet		
R16- Transformer Vault	feet		
Elements with minimum 1 foor an	d 6 inches clea	rance from roadway cafe:	
R17- Vent Infrastructure	feet		
Elements with minimum 6 inches	clearance from	roadway cafe:	
R18- Thermoplastic Marking	feet		
Roadway cafe distance from cross	swalks:		
R19- Adjacent to non-approaching side of crosswalk (min. 8 foot distance) R20- Adjacent to	feet	crosswalk on from	nce required crosswalk on paching side
approaching (stopping)		De pleases	

feet Distance required from crosswalk on non-approaching side feet feet feet

SECTION 3: Material Requirements

drawings prepared by a licensed professional.

- Please indicate which of the following materials will be part of your roadway cafe by checking the box next to the category. If applicable, please confirm the materials comply with the Dining Out NYC requirements.
- Refer to the <u>Setup Guides</u> in the Dining Out NYC website for more information regarding materials.

Materials Checklist:				
Required Barriers				
Maintained on all sides of the cafe except the side fronting the ground floor restaurant.				
Not permanently affixed to the roadway.				
30-42 inches tall (excluding planting), and at least 4 inches in width.				
Barriers are interconnected with each other.				
Any cladding over the barriers is securely fastened or affixed.				
Minimum 4 inches wide reflective strip on each barrier on the outward facing side.				
Water-filled with a minimum of 150 pounds per linear foot of barrier length.				
If your proposed barriers will utilize fill materials other than water please check this box. This may require additional information from the applicant and further review by the Dining Out NYC team, as well as supporting DOT units and City agencies.				
Optional- Only check the material categories you intend to use in your roadway cafe				
Flooring				
Durable, lightweight, easily removable, mold-resistant, elevated from the ground level to allow for drainage, and removable to allow for cleaning.				
Flush with the curb line (except if located on a slope, be flush to the greatest extent feasible), and compliant with applicable accessibility requirements.				
Maintains a 6 inch covered channel between curb and base of flooring to allow for drainage.				
<u>Furnishings</u>				
Lightweight and easily movable.				
Vertical Screenings				
Located between the barrier and 6 feet above the cafe base or floor.				
Located on the roadway facing side, does not extend the beyond the perimeter of the roadway cafe, and is not affixed to the outward facing side of barriers.				
Easily removable, comprised of non-opaque, fire-grade, and wind resistant materials.				
If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.				
Overhead Coverings/ Umbrellas				
Minimum of 7 feet and maximum of 10 feet from the base or floor of the roadway cafe.				
Has a weighted base and any support structures are not affixed to the outward facing side of barriers, are of sufficient size and strength, made of durable materials, and free of defects.				
Easily removable, comprised of fire-grade and wind resistant materials.				
If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height.				
Lighting and Electrical Connections				
Any lighting is outdoor rated, properly secured, and lightweight.				
At least 14 feet above sidewalk, and 18 feet above roadway.				
 Not attached to any City property, including street trees. Electrical work complies with the applicable requirements set forth in the DOT's rules and the New York City Electrical Code. 				
Please check this box if you are submitting additional documents for review. Documents may include technical				