



COMMUNITY BOARD FEEDBACK PACKAGE

Please review this application and provide the required feedback.

DINING OUT NYC

COMMUNITY BOARD RECOMMENDATION FORM

This form is to be used by community boards during the cafe review process. Any comments from the community board should be recorded on this form and submitted to NYC DOT. For information pertaining to specific cafe design requirements, visit the Dining Out NYC website for program legislation, rules, and Setup Guides.

Business Name: 1568 GYRO LLC Cafe Location: 1568 3RD AVE, NEW YORK, NY, 10128 Application Number: 20240724010019 CB Feedback Deadline (on date or next business day): 3/12/2025 NYCDOT Internal Use Only **Roadway Cafe Setup Comments:** Comments related to the cafe's physical footprint and dimensions: Comments related to **pedestrian flow** (i.e., visbility, safety, potential crowding): Comments related to potential conflicts with existing curb use (i.e., planters, bike racks, bus stops): Overall recommendation for the cafe setup: Suggested modifications related to the above referenced application:

RESTAURANT DETAILS

Food Service Establishment Permit(FSEP)

FSEP#: 50119449 Expiration Date: 02/28/2026

DOHMH Status: CURRENT

Business Legal Name: 1568 GYRO LLC

Assumed Name: YASOUVLAKI

Business Address: 1568 3RD AVE, NEW YORK, NY 10128

Venue Type: **Restaurant (with bar)**

Last updated from DOHMH: 01/08/2025

Restaurant Information

Entity Type: Limited Liability Corporation (LLC)

Employer Identification Number:

Phone: (929) 551-1010

Email Address: jgiampilis@gmail.com

DOS Information

DOS ID#: **7273623**

Process Name: Michael Georgoulakos

DOS Address: 30-59 Crescent Street, APT. 2R, Astoria, New York 11102

NYS Liquor Authority Information

NYSLA Serial No: **05242416349**

License Type: On-Premises

Name of License: 1568 Gyro LLC

Title of Representative: Member

Name of Certificate Holder: Ioannis Giampilis

Business hours

Sun: 11:30 AM - 9:30 PM

Mon: 11:30 AM - 9:30 PM

Tues: 11:30 AM - 9:30 PM

Wed: 11:30 AM - 9:30 PM

Thurs: 11:30 AM - 9:30 PM

Fri: 11:30 AM - 10:00 PM

Sat: 11:30 AM - 10:00 PM













SECTION 1: Site Plan

NEW YORK CITY Etc Adares
Whater
Whater
Whater
Commissions

Site Plan Form Roadway Cafe

1568 Gyro LLC

This Site Plan form is required to be uploaded in the "Roadway Site Plan" field of your online application. Refer to the How to Apply page in the Dining Out NYC website for more information about the application process.

dentify Permitted Parking Location:

- Identify the Parking Sign in front of or around the area where your roadway setup would be located. Roadway cafes can only be placed in:
- Parking spaces, which include: metered and non-metered spaces, commercial parking, alternate side parking, angled parking.
- and seasonally restricted parking.

 2. Loading areas, including loading only, truck loading, hotel loading, and no parking zones.

 3. Floating Parking Lane- a parking lane that is separated from the curb by a protected bicycle lane that is adjacent to the curb.

Use the space below to draw or upload your Site Plan representing your cafe perimeters, furniture, and clearances.

P1- Parking Space

P3- Floating Parking Lane P2- Loading Area

Restaurant Name: Applicant Name:

Yasouvlaki

FSEP Number:

50119449

Drawing Requirements

Food service establishment frontage

- shown as: space facing the sidewalk Length Label Line representing the establishment's

Labels on each street Street names:

Sidewalk shown as:

Line representing street curb

Roadway shown as:
 Width of curbside lane

Cafe perimeter shown as: Lines indicating perimeter

- Length and width

shown as: Set-up furniture (tables, chairs, etc.)

Lines or symbols at approximate

- location within setup

within 15 feet of cafe perimeter, shown Elements (in Section 2 of this form)

Lines or symbols Distance from cafe perimeter

Labels

pull boxes) shown as: Symbols representing the location within the setup

Utility coverings (water/gas valves, and

North arrow

Length of roadway cafe: feet

Width of roadway cafe: 8

feet

SECTION 2: Required Clearances

- Please provide distances from the following objects.

 Only provide a distance if the listed object is within 15 feet of your proposed setup.

 Refer to the <u>Setup Guides</u> in the Dining Out NYC website for more information regarding clearances.

	罴
	ŏ
	ě
	are
	earai
	earan
	earand
	earance
	earance
	earance
	earance t
	earance fr
	earance fro
	earance fro
	earance from
	earance from
	earance from
	earance from r
	earance from re
	earance from ro
	earance from roa
	earance from road
	earance from road
	earance from roady
	earance from roadw
	earance from roadwa
	earance from roadwa
	earance from roadway
	sarance from roadway
	earance from roadway o
	earance from roadway c
	earance from roadway ca
	earance from roadway cat
	earance from roadway cate
	sarance from roadway cafe:
TO COLUMN THE PROPERTY OF THE PROPERTY OF THE PARTY OF TH	earance from roadway cafe:
	sarance from roadway cate:
TATALOG SERVICE SERVIC	earance from roadway cafe:
THE PROPERTY OF THE PROPERTY O	sarance from roadway cafe:
	earance from roadway cafe:

	m	
R03- Subway Elevator Entrance	lements with minimum 10 fe	R01- Subway Stair: Open End
feet	eet clearance from ro	feet
R05- MTA Curb Cut	roadway cafe:	R02- Fire Hydrant
		15
feet		feet

Elements with minimum 5 feet clearance from roadway cafe:

feet

RD4-FDNY Curb Cut

R09- Subway Elevator: Non-Entry	R08- Subway Stair: Closed End	R07- Emergency Exit Hatch	R06- Curb Cut	Particular described and resolution of the property of the particular section of the particular
feet	feet	feet	feet	
R14- Drainage Infrastructure	R13-Micromobility Station	R12-Bike Corral	R11- CitiBike/Bike Share Station	B0007.000004
feet	feet	feet	feet	

Elements with minimum 3 feet clearance from roadway cafe:

R10- Bus Stop Pole:

Non- Approaching Side

feet

R17-Vent Infrastructure:	Elements with minimum 1 foor and 6 inches clearance from roadway caf	R15-Elevated Train Infrastructure
3 fe	and 6 inches	fe
et R18-Manholes	clearance from roadway cafe:	et R16-Transformer Vault
- ind		feet

Elements with minimum 6 inches clearance from roadway cafe:

grates, subway grates utility vent poles, vent

100
=
=
φ
≠
100
=
ŏ
묫
15
7
2
=
8
.2
-
1
1
1
20
3

Roadway cafe distance from crosswalks:

(min, 8 foot distance)	crosswalk	non-approaching side of	U- Adjacent to

			R21
(min. 20 foot distance)	side of crosswalk	approaching (stopping)	- Adjacent to

31

		20	
curb line of intersecting	(maintain 20 feet from	322- No crosswalk present	

street)



Check this box if none of the objects listed above are within 15 feet of the proposed setup.

SECTION 3: Material Requirements

- Please indicate which of the following materials will be part of your roadway cafe by checking the box next to the category. If applicable, please confirm the materials comply with the Dining Out NYC requirements.
- Refer to the Setup Guides in the Dining Out NYC website for more information regarding materials.

Materials Checklist:

Barriers (All of the following must be met)

- Maintained on all sides of the cafe except the side fronting the ground floor restaurant
- Not permanently affixed to the roadway.

 30.42 inches tall (excluding planting), and at least 4 inches in width
- Barriers are interconnected with each other.

- Any cladding over the barriers is securely fastened or affixed. Minimum 4 Inches wide reflective strip on each barrier on the outward facing side
- Water-filled with a minimum of 150 pounds per linear foot of barrier length.

Optional - Only check the material categories you intend to use in your roadway cafe

Flooring (if using, all of the following must be met)

- Flush with the curb line (except if located on a slope, be flush to the greatest extent feasible), and Durable, lightweight, easily removable, mold-resistant, elevated from the ground level to allow for drainage, and removable to allow for cleaning.
- compliant with applicable accessibility requirements.

Maintains a 6 inch covered channel between curb and base of flooring to allow for drainage.

- Furnishings (if using, all of the following must be met)
- Lightweight and easily movable.

Vertical Screenings (if using, all of the following must be met)

- Located between the barrier and 6 feet above the cafe base or floor.
- Located on the roadway facing side, does not extend the beyond the perimeter of the roadway cafe, and is not affixed to the outward facing side of barriers.
- Easily removable, comprised of non-opaque, fire-grade, and wind resistant materials.
- If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height

Overhead Coverings/ Umbrellas (if using, all of the following must be met)

- Minimum of 7 feet and maximum of 10 feet from the base or floor of the roadway cafe
- Has a weighted base and any support structures are not affixed to the outward facing side of barriers, are of sufficient size and strength, made of durable materials, and free of defects.
- Easily removable, comprised of fire-grade and wind resistant materials. If within 50 feet of any regulatory or warning signs, does not exceed 46 inches in height
- Lighting and Electrical Connections (if using, all of the following must be met)
- Any lighting is outdoor rated, properly secured, and lightweight
- At least 14 feet above sidewalk, and 18 feet above roadway.
- Not attached to any City property, including street trees.
- Electrical work compiles with the applicable requirements set forth in DOT's rules and the New York City Electrical Code. Please note that this may require additional permits from DOB or FDNY, and/or approval from the Landmarks Preservation Commission (LPC) as applicable.